

PNOZ X1P C 24VDC 3n/o 1n/c

787100



Safety relay (standalone) Inputs: Single-channel wiring Outputs: 3 N/O, 1 N/C. Automatic/manual reset UB 24 V DC, width: 22.5 mm, plug-in spring-loaded terminals.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;CCC
Application options:	Instantaneous E-STOP monitoring;Limit switch;Safety gate monitor
Operating modes:	Single-channel;Automatic reset;Manual reset
Product standard:	EN 60947-5-1
Standards:	EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1
Supply voltage (V):	24,0
Supply voltage type:	DC
Terminal style:	Plug-in
Terminal type:	Spring-loaded terminal
Number of instantaneous safety contacts:	3
Number of delayed safety contacts:	0
Number of auxiliary contacts:	1
Number of semiconductor outputs:	0
Stop category:	0
Max. current at DC13 I (6 cycles/min):	4.0 A
Max. current at AC15:	5.0 A
Width dimension:	22.5 mm
Height dimension:	101.0 mm
Depth dimension:	121.0 mm
Gross weight:	215 g

Net weight:	205 g
Ambient temperature:	-10 - 55 °C

Optional accessories



374290

PNOZ X Set spring loaded terminals P1+P2